

# Manufacturers of Quality Automotive Products Since 1915

## JOBBER'S PRICE LIST U. S. A.

Includes all additions on 857-D Dealers Sheet through Supplement No. 3

Prices subject to change without notice

ACME		Price	Unit Package		Suggested
Stock No.	ITEM		Quan- tity	Wt. in Lbs.	List Price Each
TR-15 TR-25 TR-35 TR-50 206 207	Rubber Valves 13%" long  " " 11%" long  " " 2½" long  " " 31%" long  Short Standard Tractor Tire Valve 127/32" long  Standard Tractor Tire Valve Long	29.40C 32.90C 35.30C 64.50C 82.10C 82.10C	10 10 10 10 10 10	10 oz. 11 oz. 12 oz. 1 11/4 11/4	.70 .85 .90 1.50 1.95 1.95
210 150MB 150BK 151MB 151BK	Valve Cores—Long type 5 in metal box  " " " —bulk—100 to carton  Valve Cores—Short type 5 in metal box  " " " —bulk—100 to carton  Please order by Stock Number.	29.40C 44.65M 42.00M 44.65M 42.00M	10 1M 500 1M 500	11 oz. 5 1½ 4¾ 1¼	.60 bx
201	Holding Tool	.36 ea.	10	11/2	
203 203 W 204 204 W 205 205 W	Screw on Repair Valves (without bridge washers)  " " " (with bridge washers)  " " " (without bridge washers)  " " " (with bridge washers)  " " " (without bridge washers)  " " " (with bridge washers)  " " " (with bridge washers)  3 Brass Bushings are included in each box of above valves.	71.50C 79.10C 70.80C 76.50C 68.00C 73.10C	25 15 25 25 25 25 25	4 3½ 3¾ 4½ 3½ 4½ 4¼	1.70 1.85 1.65 1.80 1.60 1.75
208	Core Housing for Air-Water Tractor Tire Valve	.31 ea.	10	5 oz.	.74
211	Water Adapter	.87 ea.	10	2	2.05
225BK 225D 226BK 226D 227D	Valve Stem Guards (%" diam. at base)	4.30C 4.30cd. 4.80C 4.80cd.	20 1cd. 20 1cd.	3½ oz. 1¾ 5 oz. 2	.18 .70 bg .20 .75 bg
250	Tubeless Tire Valve (Rubber Covered) DeLuxe Model with Chrome Sleeve	52.50C	1cd.	2 5½ oz.	1.37
251 260	Universal Tubeless Tire Valve (Metal) for 15" Rim	44.25C 41.30C	5 5	8 oz. 8 oz.	1.05 .95
253 254 255 256 257 258 259	Tubeless Tire Valve (Rubber Covered) Snap-In Type	25.40C 30.60C 29.30C 25.30C 26.60C 30.30C 32.80C	10 10 10 10 10 10 10	8 oz. 10 oz. 8 oz. 6 oz. 7 oz. 8 oz. 9 oz.	.65 .75 .75 .65 .65 .75 .80
253-50 254-50 255-50 256-50 257-50 258-50 259-50	Tubeless Tire Valve (Rubber Covered) Snap-In Type (Bulk Pak)  " " " " " " " " " " " " " " " " " " "	22.30C 26.80C 25.50C 22.20C 23.50C 26.50C 29.00C	50 50 50 50 50 50 50	1 <sup>3</sup> / <sub>4</sub> 2 <sup>1</sup> / <sub>2</sub> 2 1 <sup>1</sup> / <sub>2</sub> 1 <sup>3</sup> / <sub>4</sub> 2 2	.60 .70 .70 .60 .60 .70

# ACME

ACME			Unit Package		Suggested
Stock No.	ITEM	Price	Quan- tity	Wt. in Lbs.	List Price Each
261	Tubeless Tire Valve Unit (Contains: 10 Each No. 253, No. 256 Valves; 5 No. 354, 2 No. 355 Extension Caps)	5.84 ea.	1	11/4	#24494169
262	Tubeless Tire Valve Unit (Contains: 10 No. 260 Valves; 5 No. 354 Extension Caps)	4.65 ea.	1	11/4	00-00.0000
265	Tool (Insert and Remove) for Tubeless Tire Valve	1.13 ea.	1	1	drawbeama
270	Truck Tubeless Tire Valve Repair Kit	.93 еа.	5	4 oz.	
271 272 273 274 275 276	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	44.80C 46.50C 51.00C 52.50C 54.20C 60.30C	10 10 10 10 10 10	1 1 1 <sup>1</sup> / <sub>4</sub> 1 <sup>1</sup> / <sub>2</sub> 1 <sup>1</sup> / <sub>2</sub>	1.05 1.10 1.20 1.25 1.30 1.40
300PB 300BK 301PB 301BK 302BK 305PB 305BK	Valve Caps—Dome Type—5 in box	20.75M 16.00M 26.50M 21.75M 17.50M 24.50M 19.75M	1M 1M 1M 1M 1M 1M 1M	61/4 51/4 71/2 61/2 5 71/2 71/4	.30 bx5
310	Valve Cap—Dome Type—Plastic—Bulk 100 to carton	5.20M	1M	11/4	*********
348 349 351 352 353	Valve Extensions <sup>2</sup> / <sub>12</sub> " long  " " "  ½" long  " " 1  ½" long  " " 2½" long  " " 3½" long  " " 3½" long  * Does not include ½" overlap over valve to counteract centrifugal force. Overall length: 4".	11.55C 14.45C 46.20C 52.50C 77.70C	25 25 10 10 10	8 oz. 12 oz. 5 oz. 8 oz. 1	.27 .34 1.06 1.23 1.79
350PB 350BK 354 355	Air-In Extension Valve Caps—Eff. Length ½" (5 in Box)	10.40C 9.35C 10.50C 12.00C	100 50 25 25	1½ 8 oz. 8 oz. 12 oz.	1.45 bx5
354BX 355BX	4 No. 354 in Plastic Box—on Individual Card 4 No. 355 in Plastic Box—on Individual Card	.42cd. .48cd.	25cds. 25cds.	2½ 3¾	1.00 bx 1.12 bx
354D 354D 354D 355D 355D 355D 355D 355D	Air-In Extension Valve Caps—Eff. Length ¾" """""""""""""""""""""""""""""""""""	5.05cd. 4.80cd. 4.55cd. 4.32cd. 5.76cd. 5.45cd. 5.18cd. 4.92cd.	1cd. 12cds. 24cds. 48cds. 1cd. 12cds. 24cds. 48cds.	36 72 2 24 48	1.00 bx 1.00 bx 1.00 bx 1.00 bx 1.12 bx 1.12 bx 1.12 bx 1.12 bx
500 505 509 520 521 525	Cylinder Compression Gauge  Tractor Tire Pencil Gauge—5-50 lbs. (1 lb. units) Nylon Bar  Professional Tire Gauge—5-50 lbs. (1 lb. units) Nylon Bar  Pencil Gauge—20-120 lbs. (5 lb. units) Nylon Bar  Pencil Gauge for Air Lifts—1-16 lbs. (½ lb. units), nylon bar  Personal Gauge—10-40 lbs. (1 lb. units)	.95 ea. 1.05 ea. .95 ea. .95 ea. 1.15 ea. .90 ea.	1 10 10 10 10 10	2½ 1¼ 1½ 1½ 1¼ 1¼ 1½	2.25 2.52 2.25 2.25 2.25 2.95 2.00
540	Service Gauge—Brass Dual Head—Mounting Ring—10-120 lbs. Nylon Bar	2.85 ea.	5	21/2	*******
500 510 525 526	4-in-1 Valve Repair Tool—Cadmium Plated 2-in-1 " " " Valve Fishing Tool—Cadmium Plated " "	.19 ea. .12½ ea. .24 ea. .65 ea.	10 20 10 10	7 oz. 6 oz. 1	.48 .32 .61 1.56
532 533 534	Air Chuck Nozzle Blow Gun Blow Gun Extension	.30 ea. .75 ea. .25 ea.	25 10 20	3½ 2½ 2	.80 2.00 .65
533D	Blow Gun—10 mounted on display card	7.50cd.	lcd.	21/4	2.00
640 641 642 643 644	"Redi-Flo" Nozzle—¾" G. H. T.  " " ¼" Male Pipe Th.  " " (7½" Long) ¾" G. H. T.  " " Hose End Only (For High Pressure Use)  " " Nozzle (7½" Long) ¾" G. H. T.	.60 ea. .80 ea. .85 ea. .40 ea.	12 10 6 6	3 2½ 3¾ 1¾	1.50 2.00 2.93 1.52
	(For High Pressure Use)	.85 ea.	6	3¾	2.93

# ACME

ACME		-	Unit P	Suggested	
Stock No.	ITEM	Price	Quan- tity	Wt. in Lbs.	List Price Each
700	"Rite-Ring" Driveway Signal — 6-inch bell	7.50 ea.	1	23/4	
705	Replaceable Induction Coil for No. 700 Rite-Ring Signal	1.00 ea.	1	l oz.	
710	"Rite-Ring" Signal Tubing — 50 ft. length	5.00 ea.	1	6	*********
711	"Rite-Ring" Signal Tubing — 100 ft. length	10.00 ea.	1	12	
725	Acme "Super-Tuf" Air Hose-25 ft, lengths	3.85 ea.	1	4	********
725A	" " " " 25 " " " " " " " " " " " " " " "	4.15 ea.	1	4	
725B	400	4.70 ea.	1	41/2	
750 750A	Acme "Super-Tuf" Air Hose—50 ft. lengths	7.40 ea. 7.70 ea.	1	8	******
750B	" " " " " "	8.30 ea.	i	81/2	
755	Acme "Super-Tuf" Air Hose-250 ft. cont. length without				
	connections	32.75 ea.	1	42	*******
790	Brass Ferrules—1/16" I. D.—1/2" long " —1/2" I. D.—1/2" long	10.50M	100	4 oz.	*******
791	" " —½" I. D.—½" long	11.55M	100	6 oz.	********
792	" " -½" I. D½" long " " -620" I. D½" long " " -620" I. D½" long	36.00M	100	11/2	
793 794	" "640" I. D7's" long " "660" I. D7's" long	36.00M 36.00M	100	11/2	********
74	,000 1. D.—/8 1011g	30.00111	100	1½	
800	Chuck with built in Swivel	.60 ea.	10	1½	1.52
801	Screw in type male fitting single—Brass Finish	.28 ea.	10-	11/4	.73
802 803	" " double—" " " " female fitting single—" "	.45 ea.	10	13/4	1.19
,00	Tenate acting single	.20 ca.	10	174	.10
805	Pump Connection	7.35C	25	3/4	.22
806	Air Chuck male for 1/4" I. D. Hose	.38 ea.	20	2	.97
807 808	" " %6" I. D. Hose	.38 ea.	20	2 2	.97
809	" " " " " " " " " " " " " " " " " " "	.38 ea.	20 20	21/4	.97
810	" " ¼" I. P. Thread	.38 ea.	20	134	.97
815	" screw on type ¼" female pipe thread	.35 ea.	20	2	.94
816	Air Chuck Clip	1.18 ea.	10	12 oz.	
817	All Purpose Swivel	.55 ea.	10	1	1.40
825	Open Air Chuck dual head extension 1/4" female pipe thread	1.00 ea.	1	5 oz.	*********
825A	(Used on Airline Gauges and 540 Gauges)—Solid Brass Closed Air Chuck dual head extension ¼" female pipe thread	1.00 ea.	1	5 oz.	
0056	(Used on Air Meters and Air Hose)—Solid Brass				
825S	Air Chuck dual head extension with swivel—Solid Brass	1.20 ea.	1	6 oz.	*******
826 827	Kit for open dual Chuck	.40 ea. .40 ea.	1	*******	********
			000		
850 851	Brass Coupling with ¼" male pipe thread for ¼" I. D. Hose	.13 ea.	20 20	1	.35
852	" " " " " " " " " " " " " " " " " " "	.14 ea.	10	1/2	.35
853	" " " " " " " " " " " " " " " " " " "	.14 ea.	20	11/4	.35
854		.13 ea.	20	3/4	.35
860 870	Female Coupling for 1/4" I. D. Hose 1/4" I. P. Thread	.18 ea.	20	1	.43
871	" " " " " " " " " " " " " " " " " " "	.15 ea.	20 20	11/4	.35
372	Hose Repair Couplings for '4" I. D. Hose.  " " " " " " " " " " I. D. Hose.  " " " " " " " " " " " " " " I. D. Hose.	.15 ca.	20	11/4	.37
373	" " " " <u>1/2</u> " I. D. Hose	.15 ea.	10	3/4	.37
880	Repair Bushing	6.00C	10		.17
884	Air Chuck Inflating Pins and air checks	10.50C	10	********	.27
885	" "Standard Chuck Washers	.03 ea.	10		.08
886 887	Screw in Nut Standard Dual Chuck Washers	.12 ea. .03 ea.	10	********	.30
			10	********	.00
888	"Open" Dual Chuck Head Only—Without extension (Used on Airline Gauge and 540 Gauges)—Solid Brass	.68 ea.	10		*******
888A	"Closed" Dual Chuck Head Only—Without extension  (Used on Air Meters and Air Hose)—Solid Brass	.68 ea.	10		*********
889	Dual Chuck Screw In Nut	.12 ea.	10		********
890 891	"Closed" Inflating Pin Air Check for Dual Chuck "Open" Inflating Pin Air Check for Dual Chuck	.08 ea.	10 10	*******	********
900	Any 900B Series Coupler Body furnished with any 900N Series	.oo ca.	10	*******	*********
	Nipple—complete	.85 ea.	10	21/2	2.40
900B	Through 904B inclusive, (coupler bodies only)	.75 ea.	10	2	2.10
900N 901N	1/4" Female Pipe Thread—Nipple only	.16 ea.	10	1/2	.45
902N	14" Male Pipe Thread — " " 18" Female Pipe Thread— " " 18" Male Pipe Thread — " "	.16 ea.	10	1/2 1/2	.45
903N	1/8" Male Pipe Thread — " "	.16 ea.	10	1/2	.45
904N	Hose Barb for 1/4" I. D. Hose—Nipple only	.16 ea.	10	1/2	.45

### ACME

ACME			Unit Package		Suggested
No.	ITEM	Price	Quan- tity	Wt. in Lbs.	List Price Each
905 906 907 908 909	Adapters ¼" Double Male I. P. Thread  " ¼" Female, ½" Male I. P. Thread  " ¼" " ¾" Male I. P. Thread  " ¾" " ¼" Male I. P. Thread  " ¼" Double Female I. P. Thread	14.00C 11.75C 15.50C 20.50C 14.00C	10 10 10 10 10	10 oz. 7½ oz. 7½ oz. 1⅓ 10 oz.	.35 .29 .38 .51
1000 1000 1000	(Model R) Airline Gauge — with 1030 Hose — 10-120 lbs	6.30 ea. 6.80 ea. 7.35 ea.	1 1 1	2 2 2	despecials despecials
1020 1025 1025D 1030	Airline Gauge Hose Assembly with ¼" male pipe fitting	1.00 ea. 1.35 ea. 2.00 ea. 1.60 ea.	1 1 1	6 oz. 1/2 3/4 1/2	processo processo accessos
1025L	Hose Assembly 48" Long for 2550 Tank	1.70 ea.	1	3/4	40000000
1100 1150	Adjust-O-Matic Electric Vulcanizer A.C. for 110-120 Volts	11.80 ea. 6.55 ea.	1 1	8 1½	********
2500 2550 2551	Air Storage Tank (8" x 16")—3¼ Gal. Cap. " " (12" x 20")—9 Gal. Cap. Tank Gauge	11.85 ea. 19.40 ea. 1.65 ea.	1 1 1	14 30	***************************************
2570 2575	Air Tank Valve—1/8" P. T. At Bottom——————————————————————————————————	.18 ea. .18 ea.	10 10	6 oz. 6 oz.	.50 .50
2600 2600 2600 2600	Drain Cock Assortment—24 pcs. on Display Card	2.90cd. 2.75cd. 2.60cd. 2.25cd.	1cd. 10cd. 25cd. 50cd.	1½ 15 38 75	01000000 40000000 90000000
2601 2602 2603 2604 2605	Drain Cocks (Bulk)	9.00C 12.00C 17.00C 21.00C 17.00C	10 10 15 15 15	5 oz. 8 oz. 1 1½ 1	.30 .40 .60 .70 .60
2610 2610	Drain Cock Ass't (12 No. 2601, 12 No. 2602) on Display Card	2.28cd. 1.90cd.	1cd. 50cds.	1½ 75	********
2611 2612	Drain Cock Assortment — 24 pcs. on a display card: 6 No. 2601 and 18 No. 2602  Drain Cock Assortment — 24 pcs. on a display card: 24 No. 2602	3.00 cd. 3.15 cd.	1	1½ 1½	eposition

#### AIRLINE GAUGE REPAIR PARTS

1	Aluminum Housing Only-No Parts	2.25 ea.	20	Valve Port Washer	.03 ea.
2	Back End Plugs	.20 "	24	Air Check Springs	.05 "
3	Piston Retainer	.20 "	26	Air Valve Packing Retaining Spring	.05 "
4	Port Plug	.15 "	29	Pressure Spring	.25 "
5	Front End Plug	.20 "	S-1	Piston Assembly	.50 "
7	Pressure Indicator	.25 "	S-2	Screen	.05 "
8	Crystal	.15 "	S-3	Rubber Bumpers	.20 "
9	Snap Ring	.03 "	S-5	Air Valve Assembly	.30 "
16	Indicator Pointer	.10 "	S-6	Gauge Valve Assembly	.30 "
19	Back End Plug Washer	.03 "	S-7	Air Check	.15 "

Printed in U. S. A.

GUARANTEE: All parts are guaranteed against defects in material and workmanship. No merchandise may be returned without our written permission.

TERMS:

2% 10th Prox., Net 25th Prox.

FREIGHT POLICY:

Freight Allowed on Single Purchase Orders of \$300.00 or More. Otherwise, F.O.B. Factory.

## ACME AIR APPLIANCE COMPANY, Inc.

205 Newman Street, Hackensack, N. J.

#### U. S. WAREHOUSES

2631 COMMERCE ST. | 1406 S. GRAND AVE. | 1355 BUSH STREET | 1138 — 8TH ST. | 61 EAST 7TH ST., SO. | 1110 EAST PIKE ST. DALLAS 26, TEXAS | LOS ANGELES 15, CAL. | SAN FRANCISCO, CAL. | DENVER 4, COLO. | SALT LAKE CITY, UTAH | SEATTLE 22, WASH.

S. F. BACHER & CO. LTD., 44 YORK ST., TORONTO 1, CANADA





Supplement No. 4

Supersedes previous supplements

# Manufacturers of Quality Automotive Products Since 1915 JOBBER'S PRICE LIST U. S. A.

Effective June 1, 1959

Prices subject to change without notice

ACME Stock No.	ITEM	Price	Unit Package  Quan- tity Ut. in Lbs.		Suggested List Price Each
TR-13	Tube-Type Valve for 14" Tubes—cold or hot application	30.00 C	10	3/4	.70 ea.
263	Kit to Adapt No. 260 for oval applications	.25 ea.	5	5¼ oz.	
881	Rim Nut for No. 206 Tractor Valve	4.40 C	20	4½ oz.	.10½ ea.
1000	(Model C) Airline Gauge—with 1031 hose assembly—10-120 lbs.	8.20 ea.	1	2	Escardousee
1031	Hose Assembly 3 ft. long equipped with a No. 815 chuck combined with a No. 816 chuck clip	3.50 ea.	1	11 oz.	Manadopayou

Printed in U. S. A.

GUARANTEE: All parts are guaranteed against defects in material and workmanship.

No merchandise may be returned without our written permission.

TERMS: 2% 10th Prox., Net 25th Prox.

FREIGHT POLICY: Freight Allowed on Purchase Orders of \$300.00 Net or More.
Otherwise F.O.B. Our Factory.

## ACME AIR APPLIANCE COMPANY, Inc.

205 Newman Street, Hackensack, N. J.

VALVE CORES • VALVE CAPS • AIR CHUCKS • AIR HOSE COUPLERS • AIR HOSE • COUPLINGS • VULCANIZERS • AIRLINE, PENCIL, TRACTOR, & SERVICE TIRE PRESSURE GAUGES • AIR STORAGE TANKS • RITE-RING DRIVEWAY SIGNAL & TUBING • TANK VALVES • VALVE TOOLS • FISHING TOOLS • BLOW GUNS • NOZZLES • REPAIR VALVES • RUBBER VALVES • DRAIN COCKS • SCREW FITTINGS • TUBELESS TIRE VALVES • VALVE EXTENSIONS.



